

# HIGH PERFORMANCE LASER-RADAR DETECTOR

## PRO-68XRi



**Order Number** PRO-68XRi

**MSRP** \$179.95

**Unit Dimensions** 1.4 in. H x 3.15 in. W x 4.9 in. L

**Unit Weight** 6.5 oz.

**Packaging** Box

**Retail Packaging Dimensions** 6.06 in. H x 7.81 in. W x 2.25 in. D

**Retail Weight** 14.4 oz

**UPC** 0 52303 40565 5

**Case Pack Quantity** 3

**Case Pack Dimensions** 6.38 in. H x 7 in. W x 8 in. L

**Case Pack Weight** 3 lbs.

**Case Cube** .21

**Accessories** Windshield Bracket Kit, Dash Pad, Power Cord, Hardwire Kit, Manual

Whistler laser-radar detectors receive laser guns that operate at a laser wavelength of 800 - 1000nm.

Whistler detectors receive the following radar frequencies:

10.500 - 10.550 GHz	X Band
24.050 - 24.250 GHz	K Band
33.400 - 36.000 GHz	SuperWideBand Ka
34.0, 34.3, 35.5 GHz	Ka Narrow Plus

This includes the POP™ instant-on feature, which operates within the K and Ka bands. POP™ is a trademark of MPH Industries.

One or more U.S. patents may apply:  
#7,215,276

## FEATURES:

**HIGH PERFORMANCE** provides extra detection range for advanced warning

**Ka NARROW PLUS MODE** looks only for the following Ka Frequencies: 34.0 GHz, 34.3 GHz and 35.5 GHz

**DETECTS EUROPEAN LASER GUNS** (Traffipatrol XR, Riegl, Jenoptik, Laveg, Truspeed and more)

**SELECTABLE LASER MODES** allow selection of multiple pulse rate segments including **TRAFFIPATROL XR**, **LISD**, and laser guns with **STEALTH MODES**

**X/K FILTER MODES** offer multiple levels of rejection to reduce false alerts caused by Radar Traffic Monitoring Systems including radar based lane change assistant

**Ka FILTER MODES** offer multiple levels of signal processing to reduce false alerts caused by some radar detectors

**BLUE NUMERIC ICON DISPLAY** provides distinct visual symbols of alerts detected and engaged modes. Signal strength is shown as a number (1-9)

**POP™ MODE DETECTION** advanced speed detection capability responds to brief bursts of radar

**ALERT PERISCOPES** LED's on top of the unit provide additional visual alert

**360° MAXX COVERAGE** detects from front, sides, and rear

**3 CITY MODES** (City, City 1, City 2) reduce the annoyance of false alerts

**HIGH GAIN LENS** provides increased field of view

**SELECTABLE BANDS** allow specific bands to be turned on or off

**STAY ALERT®** Whistler's exclusive feature that tests your alertness on long trips

**DIM / DARK MODE** reduces the illumination of the display. When in dark mode, the display is turned off during an alert then remains off for 20 more seconds before returning to its dimmer setting.

**QUIET / AUTO QUIET MODE** silences audio alerts

**ALERT PRIORITY** displays most important signal when more than one is detected

**SETTING SAVER** saves personalized settings when unit is turned off

**VEHICLE BATTERY SAVER** automatically shuts off your detector if you forget to turn it off

**SAFETY WARNING SYSTEM™** keeps you informed of highway safety where transmitters are located

**INTELLICORD® READY** capable of working with optional INTELLICORD® power cord

**HARDWIRE KIT** safely connect power to your device from your fuse box



[www.whistlergroup.com](http://www.whistlergroup.com) | 479.273.6012

©2011 The Whistler Group, Inc.  
3604 NW Frontage Road | Bentonville, AR 72712

